

Radial Pneus 6 - 7H - 8

The RP 6 presses allow to retread tyres for agricultural purpose, aircraft and small OTR.

The presses can be manufactured tubeless, bladder, curing tube and with high belt to increase the tyre width range



Technical features*

	RP6	RP7H	RP8
Ø DIAMETER OF THE CAVITY mm	1550	1750	1950
HEIGHT OF THE CAVITY mm	550/600	470/700	700/850
MAX TYRE O.D. mm	1490	1690	1880
MAX TYRE C.S. mm	580	670	820
WEIGHT Kg	11000	12000	22000
AIR CONSUMPTION Nlt/h	3500	3500	7500
STEAM CONSUMPTION Kg/h	80	100	130
MAX INFLAT. PRESSURE Bar**	18	18	18
ENGINE POWER HP	5.5	7.5	10
WIDTH mm	3300	3300	3500
LENGTH mm	3900	3900	4300
CLOSED HEIGHT mm	1450	1800	2500
OPEN HEIGHT mm	3250	3850	5000
TYRES SIZES	From 13.00R 20 to 20.5 R 25	From 14.00 R 24 to 23.5 R 25	Up to 29.5 R 25

**standard configuration. Higher pressures on request

Radial Pneus 9 - 9H and 10

The RP 9 an 10 presses allow to retread tyres for agricultural purpose, aircraft and OTR.

The presses can be manufactured tubeless and with curing tube.



Technical features*

	RP 9	RP 9 H	RP 10
Ø DIAMETER OF THE CAVITY mm	2150	2150	2500
HEIGHT OF THE CAVITY mm	750/850	800/1000	800/1100
MAX TYRE O.D. mm	2080	2080	2420
MAX TYRE C.S. mm	820	970	1050
WEIGHT Kg	25000	29000	32000
AIR CONSUMPTION Nlt/h	7500	8000	10000
STEAM CONSUMPTION Kg/h	150	180	230
MAX INFLAT. PRESSURE Bar**	18	18	14
ENGINE POWER HP	10	10	12,5
WIDTH mm	3500	3500	3900
LENGTH mm	4700	4700	5300
CLOSED HEIGHT mm	2500	2650	2800
OPEN HEIGHT mm	5000	5150	5500
TYRES SIZES	From 23.5 R 25 to 29.5 R 29	From 23.5 R 25 to 35/60 R 33	From 24.00 R 35 to 37/25 R 35

**standard configuration. Higher pressures on request

*Dimensions and specification shown are not binding and could be changed without notice by the manufacturer

Radial Pneus 11 and 14

The RP 11 and RP 14 presses allow to retread tyres for big OTR tyres

The presses can be manufactured tubeless



Technical features*

Ø DIAMETER OF THE CAVITY	mm
HEIGHT OF THE CAVITY	mm
MAX TYRE O.D.	mm
MAX TYRE C.S.	mm
N. OF SEGMENTS	
AIR CONSUMPTION	Nlt/h
STEAM CONSUMPTION	Kg/h
MAX INFLAT. PRESSURE	Bar
ENGINE POWER	HP

RP 11

3100
1250
2850
1160
12
12000
250
13
30

RP 14

4250
1600
4030
1500
12
15000
300
13
40

TYRES SIZES

From 35" to 49"
incl. 45/65R45 and
27.00R49

From 57" tp 63"
incl. 40.00R57 and
59/80R63